

# ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804+A1 for:

**FKD N Thermal, SmartWall N C1, SmartWall N C2,  
MW Dammplatte 034 Evo, MW Dammplatte 034  
Evo+**

From

**KNAUF**INSULATION



Program:	The International EPD® System <a href="http://www.environdec.com">www.environdec.com</a>
Programme operator:	EPD International AB
EPD registration number:	S-P-01882
Publication date:	2020-07-06
Validity date:	2025-07-06
Version number:	2
Date of update:	2022-12-23

**EPD**®

EPD SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+



challenge.  
create.  
care.

## Programme-related information and verification

The EPD owner has the sole ownership, liability, and responsibility for the EPD. EPDs of construction products may not be comparable if they do not comply with EN 15804+A1 and if the building context, respectively the product-specific characteristics of performance are not taken into account.

<b>Programme:</b>	The International EPD® System EPD International AB Box 210 60 SE-100 31 Stockholm Sweden <a href="http://www.environdec.com">www.environdec.com</a> <a href="mailto:info@environdec.com">info@environdec.com</a>
<b>EPD registration number:</b>	S-P-01882
<b>Published:</b>	2020-07-06
<b>Valid until:</b>	2025-07-06
<b>EPD owner</b>	Knauf Insulation Sprl Rue de Maestricht 95 4600 Visé Belgium
<b>Product Category Rules:</b>	PCR 2012:01. Construction products and construction services. Version 2.3 Sub-PCR-I Thermal insulation products (EN 16783: 2017).
<b>Product group classification:</b>	UN CPC 37
<b>Reference year for plant data:</b>	2018
<b>Geographical application scope:</b>	Europe

CEN standard EN 15804+A1 serves as the Core Product Category Rules (PCR)
Product category rules (PCR): Construction products and Construction services, 2012:01, version 2.3, UN CPC 37. Sub-PCR-I Thermal insulation products (EN 16783: 2017),
PCR review was conducted by: The Technical Committee of the International EPD® System
Independent third-party verification of the declaration and data, according to ISO 14025:2006.
<input checked="" type="checkbox"/> EPD process certification <input type="checkbox"/> EPD verification
Certified by: Bureau Veritas certification Sverige AB SE006629-1
Procedure for follow-up of data during EPD validity involves third party verifier:
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

## General information

### Information about the company

#### Description of the organisation:

Knauf Insulation has more than 40 years of experience in the insulation industry and is one of the most respected names in insulation worldwide. Knauf Insulation is manufacturing products and solutions mainly in glass and rock mineral wool, as well as wood wool. We operate more than 37 manufacturing sites globally in 15 countries and employ more than 5,000 people. The Headquarters are located in Visé, in Belgium.

#### Product-related or management system-related certifications:


All Knauf Insulation sites, including the related site for this EPD, are ISO 9001, ISO 14001, ISO 5001 and ISO 45001 certified under the scope "Design, Development and Production of Insulation Materials and Systems".

### Information about Rock Mineral Wool production

The Rock Mineral Wool Products for Building Construction are available in the form of slabs, boards, lamellas and rolls. RMW slabs are used as a thermal, acoustical and fire insulation product. Knauf Insulation adopts a "worst case" approach into its EPDs.

In general, the density for rock mineral wool products ranges from 20 to 200 kg/m<sup>3</sup>. In terms of composition, the inorganic part (92-98%) is composed of volcanic rocks, typically basalt, and some dolomite and with an increasing proportion of recycled material in the form of briquettes, a mix of stone wool scrap, other secondary materials and cement.

The remaining fraction is the thermo set resin binder.



## Product information

**Product(s) names:** SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+

**Product identification:** The declared insulation product is/are SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+, a rock mineral wool, uncoated, one side coated and both sides coated surface, unfaced slab of 1 square meter (considered for this EPD). It needs a Declaration of Performance taken into consideration the harmonized product standard EN 13162 and the CE mark.

For the placing on the construction products market in the European Union/ EFTA (with exception of Switzerland), the Regulation/ (EU) No 305/2011/ applies. The concerned products need Declarations of Performance /DoP R4308MPCPR/ taking into consideration the harmonized product standard /EN 13162/ and the /CE-mark/.

**Product description:** The main application for SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ is ETICS (External Thermal Insulation Composite Systems).

## LCA information

### Functional unit / declared unit:

The declared unit is 1 square meter of unfaced, both sides coated Rock Mineral Wool SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ with a thickness of 100mm. The declared lambda is 0.034 W/mK. The density used for the calculation of this specific LCA is 90kg/m<sup>3</sup>.

**Reference service life:** The RSL or durability of SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ is as long as the lifetime of the building equipment in which it is used (at least 50 years).

### UN CPC code:

37990: Non-metallic mineral products (including mineral wool, expanded mineral materials, worked mica, articles of mica, non-electrical articles of graphite or other carbon and articles of peat).

**Geographical scope:** The product is produced in Nova Bana (Slovakia) with related country energy mix for electricity. Regarding the market area, the product is marketed in Europe.

### Energy:

Electricity mix and gas inputs are taken from related country values taken from reference year 2015.

### Technical Characteristics:

Parameter	Value
Thermal conductivity/ EN 12667	0.034 W/(mK) at 10°C
Water vapor diffusion resistance (EN 12086)	1
Thermal Resistance (ISO 8301)	2.90 m <sup>2</sup> K/W
Reaction to fire (EN 13501-1)	A1 (EN 1350-1)
Declared density range/ EN 1602	90 kg/m <sup>3</sup> (+/-10%)
Melting point of fibers DIN 4102-17	≥ 1000°C


### Time representativeness:

Plant production data for the complete year 2018.

### Database(s) and LCA software used:

The LCA model, the data aggregation and environmental impacts are calculated with the software GaBi 9.2.1 and its Service Pack 40 databases.

## System diagram:



## Description of system boundaries:

The system boundary of the EPD follows the modularity approach defined by the /EN 15804+A1/.

### The type of EPD is cradle-to-grave.

List and explanation of the modules declared in the EPD.

#### The product stage (A1-A3) includes:

- A1 - raw material extraction and processing, processing of secondary material input (e.g. recycling processes),
- A2 - transport to the manufacturer and
- A3 - manufacturing.

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of-waste state or disposal of final residues during the product stage.

The LCA results are given in an aggregated form for the product stage, meaning that the modules A1, A2 and A3 are considered as a unique module A1-A3.

Product Parameters	Value
Declared Density	90 kg/m <sup>3</sup>
Rock mineral wool weight (without coating)	9.0 kg
Surface	1 m <sup>2</sup>
Thickness	100 mm
Volume	0.1 m <sup>3</sup>
Coating	0.4 kg
Packaging Plastic sheet	0.1 kg
Packaging Wooden pallet	1.04 kg

### The construction process stage includes:

- A4 - transport to the construction site and
- A5 - installation into the building.

The transport to the building site (A4) and installation (A5) included in this LCA use the following parameters:

Parameter	Value
Average transport distance	600 km
Type of fuel and vehicle consumption or type of vehicle used for transport.	Truck. Euro 6 (28 – 32 t / 22 t payload). 33 L for 100 km.
Truck capacity utilization (including 30% of empty returns)	34% of the weight capacity
Loss of materials in construction site	2%
Packaging Wooden pallet	100% incinerated
Packaging Plastic sheet	40% recycled, 60% incinerated

The treatment of the packaging waste after the installation of the product (A5) has been considered.

### The Use stage (B1-B7) includes:

- B1: Use
- B2: Maintenance
- B3: Repair
- B4: Replacement
- B5: Refurbishment
- B6: Operational Energy Use
- B7: Operational Water Use

Once installation is complete, no actions or technical operations are required during the use stages until the end of life. Therefore, the mineral wool has no impacts (excluding potential energy savings) on this stage.

### The end-of-life stage includes:

- C1 - de-construction, demolition,
- C2 - transport to waste processing,
- C3 - waste processing for reuse, recovery and/or recycling and
- C4 - disposal.

This includes provision of all transports, materials, products and related energy and water use. The common manual dismantling impact of insulation is considered as very small and can be neglected in C1.

Although Rock Mineral Wool products from Knauf Insulation can be recycled at their end-of-life, an established collection system does not yet exist in every country.

Therefore, the assumption chosen in this study, 100% landfill (C4) after the use phase, is the most conservative approach.

Parameter	Value
Disposal type (mineral wool)	100% landfill
Average transport distance waste (C2)	50 km
Type of fuel and vehicle consumption or type of vehicle used for transport.	Truck-trailer, Euro 3, 34 - 40t gross weight / 27t payload capacity/ 40 L for 100 km. (if 100 % utilization).
Truck capacity utilization	70 % of the weight capacity

**Module D** includes reuse, recovery and/or recycling potentials. According to /EN 15804+A1/, any declared benefits and loads from net flows leaving the product system not allocated as co-products and having passed the end-of waste state shall be included in module D. Benefits considered in module D originate from packaging recycling or incineration.

### Content Declaration

The product does not contain substances on the "Candidate List of Substances of Very High Concern for Authorisation" under the REACH regulation (if above 0.1% of the mass).

### Recycled material

The mineral wool waste that is originating from the manufacturing process is recycled internally through the use of briquettes (mineral wool waste and additional cement) that are reinjected into the batch. The external recycled waste as raw material is 28% originating (mainly) from slags. The calculation is done following EN 15804+A1 Use of Resources indicator Secondary Material (SM), taking into account the % of secondary materials from external

supply input into the batch against virgin raw materials supply. The external waste considerations are also following the ISO 14021 norm.

### Additional information:

All raw materials for the manufacturing of the declared product, the required energy, water consumption and the resulting emissions are considered into the LCA. Consecutively, the recipe components with a share even less than 1% are included. All neglected processes contribute less than 5% to the total mass or less than 5% to the total energy consumption. For information, the impact of the Rock Mineral Wool plant construction or machines, are not taken into account in the life cycle assessment. No allocation is carried out for this specific product.

### Differences versus previous versions:

A clarification about recycled content details (methodology used for the calculation), in "Recycled Material" stage has been added.

### More information:

[www.knaufinsulation.com](http://www.knaufinsulation.com)  
<http://www.knaufinsulation.sk/en>  
<https://www.knaufinsulation.it/>

### Name and contact information of LCA practitioner:

Yaprak Nayir  
 Knauf Insulation Sprl  
 Rue de Maestricht 95  
 4600 Visé  
 Belgium  
 Contact: [yaprak.nayir@knaufinsulation.com](mailto:yaprak.nayir@knaufinsulation.com)

Scope:

Life cycle stages as defined in the European standard EN 15978 :2011 and the description of the system boundaries for the reference product LCA (X = included in the LCA, MND = module is not declared)

Product stage			Construction process stage		Use stage								End of life stage				Resource recovery stage
Raw materials	Transport	Manufacturing	Transport	Construction Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse- Recovery- Recycling - potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	



## Environmental performance

**Potential environmental impacts:** 1 m<sup>2</sup> of Rock Mineral Wool SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ with a thickness of 100 mm.

PARAMETERS	UNIT	TOTAL A1-A3	A4	A5	TOTAL B1-B2-B3-B4-B5-B6-B7	C1	C2	C3	C4	D*
Global warming potential (GWP)	kg CO2 eq.	9.26	0.672	2.42	0	0	0.0325	0	0.128	-0.853
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC 11 eq.	1.49E-11	1.09E-16	1.76E-10	0	0	5.39E-18	0	7.06E-16	-3.22E-14
Acidification potential (AP)	kg SO2 eq.	0.0946	0.00126	0.00211	0	0	0.000139	0	0.000823	-0.00103
Eutrophication potential (EP)	kg PO43- eq.	0.00269	0.000303	9.81E-05	0	0	3.44E-05	0	9.27E-05	-0.000131
Formation potential of tropospheric ozone (POCP)	kg C2H4 eq.	0.00486	0.000141	0.000116	0	0	1.26E-05	0	6.19E-05	-9.86E-05
Abiotic depletion potential – Elements	kg Sb eq.	7.93E-06	5.53E-08	1.81E-07	0	0	2.73E-09	0	4.95E-08	-1.57E-07
Abiotic depletion potential – Fossil resources	MJ, net calorific value	146	9.06	3.29	0	0	0.447	0	1.82	-13

\*: [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].



**Use of resources:** 1 m<sup>2</sup> of Rock Mineral Wool SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ with a thickness of 100mm.

PARAMETER		UNIT	TOTAL A1-A3	A4	A5	TOTAL B1-B2-B3-B4-B5-B6-B7	C1	C2	C3	C4	D*
Primary energy resources – Renewable	Use as energy carrier	MJ, net calorific value	12.375	0.51	0.368	0	0	0.0252	0	0.245	-2.88
	Used as raw materials	MJ, net calorific value	15.625	0	0.000	0	0	0	0	0	0
	TOTAL	MJ, net calorific value	28	0.51	0.368	0	0	0.0252	0	0.245	-2.88
Primary energy resources – Non-renewable	Use as energy carrier	MJ, net calorific value	143.046	9.09	3.418	0	0	0.448	0	1.88	-15.4
	Used as raw materials	MJ, net calorific value	10.954	0	0.132	0	0	0	0	0	0
	TOTAL	MJ, net calorific value	154	9.09	3.55	0	0	0.448	0	1.88	-15.4
Secondary material	kg	2.55	0	0.051	0	0	0	0	0	0	0
Renewable secondary fuels	MJ, net calorific value	4.33E-19	0	8.66E-21	0	0	0	0	0	0	-6.20E-25
Non-renewable secondary fuels	MJ, net calorific value	5.08E-18	0	1.02E-19	0	0	0	0	0	0	-7.29E-24
Net use of fresh water	m <sup>3</sup>	0.039	0.000591	0.00607	0	0	2.91E-05	0	0.000473	0	-0.00341

\*: [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].

**Waste production and output flows:** 1 m<sup>2</sup> of Rock Mineral Wool SmartWall N C1, SmartWall N C2, FKD N Thermal, MW Dammplatte 034 Evo, MW Dammplatte 034 Evo+ with a thickness of 100mm.

**Waste production**

PARAMETER	UNIT	TOTAL A1-A3	A4	A5	TOTAL B1-B7	C1	C2	C3	C4	D*
Hazardous waste disposed	kg	3.44E-07	4.23E-07	6.31E-09	0	0	2.09E-08	0	2.86E-08	-6.01E-09
Non-hazardous waste disposed	kg	0.82	0.00139	0.221	0	0	6.86E-05	0	9.43	-0.00637
Radioactive waste disposed	kg	0.00329	1.12E-05	0.000104	0	0	5.55E-07	0	2.13E-05	-0.000972

**Output flows**

PARAMETER	UNIT	TOTAL A1-A3	A4	A5	TOTAL B1-B7	C1	C2	C3	C4	D*
Components for reuse	kg	0	0	0	0	0	0	0	0	0
Material for recycling	kg	0	0	0.0422	0	0	0	0	0	0
Materials for energy recovery	kg	0	0	0	0	0	0	0	0	0
Exported energy, electricity	MJ	0	0	0.334	0	0	0	0	0	2.85
Exported energy, thermal	MJ	0	0	1.1	0	0	0	0	0	5.12

\*: [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].

## LCA interpretation

### ENVIRONMENTAL IMPACTS

All impact categories, except the Abiotic Depletion Potential Element and the Ozone Depletion Potential, are dominated by the production processes. This can be explained by the huge impact of the energy use (electricity, natural gas and coke) for Rock Mineral Wool production.

**The Global Warming Potential (GWP)** is dominated by the production in the cupola, mostly due to CO<sub>2</sub> emissions from raw materials and energy consumption (50%). The production of the binder represents more than 15% of the impact.

**The Ozone layer Depletion Potential (ODP)** results are under the high influence of the selected scenario for plastic sheets packaging incineration.

**The Acidification Potential (AP)** is also dominated by the production due to the emissions related to the processes and the energy consumption.

**The Eutrophication Potential (EP)** is significantly influenced by the production due to emissions from cupola furnace, curing oven and other unit processes.

**The Photochemical Ozone Creation Potential (POCP)** is particularly dominated by the production (emissions in the cupola furnace and other unit processes).

**The Abiotic Depletion Potential Element (ADPe)** is mainly due to the cement utilized in the briquettes production process in order to recycle secondary materials from the lines, the briquettes are reinjected into the melting batch. The impact of the raw materials in general, like the volcanic rock basalt, is very minor as this material is very abundant on Earth. The thermo set resin binder has also important impact on ADPe indicator due to the fossil origin.

**The Abiotic Depletion Potential Fossil (ADPf)** is dominated by the use of coke as energy carrier. Next to the coke, we have also the impact of natural gas and upstream the electricity energy mix.

### RESOURCES USE

**Total Use of Non-Renewable Primary Energy Resources (PENRT)** is dominated by the production of rock mineral wool products (especially due to the energy carrier, coke) and the binder.

**Total Use of Renewable Primary Energy Resources (PERT)** is dominated by the production, mostly due to electricity consumption and packaging.

**For the Use of Secondary Material (SM)**, it consists of slags and some minor mineral wool external waste are also considered.

## References

### International EPD® System

General Programme Instructions of the International EPD® System. Version 2.5.

Product Category Rules PCR 2012:01. Construction products and construction services. Version 2.3

Sub-PCR-I Thermal insulation products (EN 16783: 2017).

#### ISO 14021

ISO 14021:2016. Environmental labels and declarations — Self-declared environmental claims (Type II environmental labelling)

#### ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

#### EN 15804

EN 15804:2012-04+A1 2013: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

#### GaBi 9.2

GaBi 9.2: Software and database for life cycle engineering. LBP, University of Stuttgart and PE INTERNATIONAL AG, 2019.

#### EN 1602:

EN1602: 2013 Thermal insulation products for building applications – Determination of the apparent density

#### EN 12667

EN 12667: 2001 Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Products of high and medium thermal resistance

#### EN 13162

EN 13162:2012 Thermal insulation products for buildings - Factory made mineral wool (MW) products - Specification

#### EN 13501-1

EN 13501-1: 2009 Fire classification of construction products and building elements - Part 1: Classification using test data from reaction to fire tests.

#### DIN 4102 / T17

DIN 4102 / T17: 1990 Fire behaviour of building materials and elements; determination of melting point of mineral fibre insulating materials; concepts, requirements and testing.

#### EN 12086

EN 12086: 2013 Thermal insulating products for building applications –determination of water vapour transmission properties.

**ISO 8301:1991**

Thermal insulation — Determination of steady-state thermal resistance and related properties — Heat flow meter apparatus.

**EN 15978: 2011**

EN 15978: 2011 Sustainability of construction works - Assessment of environmental performance of buildings - Calculation method.

**DoP R4308MPCPR**

Declaration of Performance – [www.dopki.com](http://www.dopki.com)

## Contact information:

EPD owner:	 <p>Knauf Insulation Rue de Maestricht 95 4600 Visé Belgium <a href="http://www.knaufinsulation.com">www.knaufinsulation.com</a> Contact: <a href="mailto:sustainability@knaufinsulation.com">sustainability@knaufinsulation.com</a></p>
LCA support:	 <p>Université de Liège – Laboratory of Chemical Engineering PEPs - Products, Environment and Processes Allée du 6 août 15, Bat B6 4000 Liège Belgium</p>  <p>Thinkstep Hauptstraße 111-113 70771 Leinfelden-Echterdingen Germany</p>
Programme operator:	 <p>EPD International AB <a href="mailto:info@environdec.com">info@environdec.com</a></p>